

RICOH

Caplio R40

Beautiful photographs make precious memories timeless.

28-160mm
optical 5.7x zoom

Effective megapixel
6.04 CCD

2.5-inch
153,000 pixels
LCD monitor

Battery power lasts
approx. 350 shots^{*1}

1cm
macro

Top shutter
release time lag:
0.007sec.^{*2}

Optical 5.7x zoom moves you closer.



28mm wide angle

160mm telephoto



While a 105mm zoom only gives you this perspective, the Caplio R40 shows you much more. Stretching all the way from wide-angle 28mm to 160mm, our 5.7x optical zoom delivers more power to preserve your most precious memories.



105mm telephoto

*1 Battery performance was measured using CIPA-standard parameters. Actual performance may vary according to usage conditions and the brand of the battery.
*2 Shutter release time lag with focus lock engaged. * Focal lengths are 35mm film camera equivalents.

A higher level of features. The same slim size.

Amazing macro photography for eye-opening views

Set your lens to its widest angle and you can shoot as close as 1cm away from your subject! For an even more powerful perspective, use telemacro up to 8cm away. Using the four direction buttons—▲▼◀▶—in AF Target Selection, you can also shift the focus point without moving your camera.



● 1cm macro

0.007-second shutter release time lag*

The Caplio R40's ultra-high-speed response keeps you ready for action. Powering up takes

1.1 seconds, shutter release time lag is approximately 0.09 seconds (without focus lock engaged), and your camera resets for the next shot in half a second.

* Approx. time with focus lock engaged
* Time measurements with flash OFF

Large 2.5-inch High Quality LCD Monitor (153,000 pixels)

The large 2.5-inch LCD monitor allows for clearer, more detailed and defined shooting and playback of images.



Image is simulated

● 2.5-inch LCD monitor

Double Retracting LENS System fits a powerful lens inside a slim body

How does a 5.7x optical zoom lens fit inside a slim 26mm camera? As the lens retracts, part of it swings like a pendulum inside the camera. Ricoh's advanced Double Retracting LENS System—a smart solution for a smart design.



● Double Retracting LENS System

Additional features & functions

- Skew correction function—handy for business uses
- Eight scene modes
- Three continuous shooting modes
- Shoot video with digital zoom and sound until memory is full

Image is simulated **Champagne**

Image is simulated **Black**

⑥

⑤

④

③

①

②

⑥

〈Accessories Included〉

- ① USB Cable
- ② AV Cable
- ③ CD-ROM
- ④ Hand Strap
- ⑤ Rechargeable Lithium-Ion Battery: DB-60
- ⑥ Battery Charger: BJ-6

● Instruction Manuals (Camera, Introduction)*

Warranty Card

* Software manual supplied on CD-ROM

Caplio R40 Major Specifications

Item	Description
CCD	Effective pixels 6.04 million (Total 6.18 million pixels), 1/2.5-inch primary color CCD
Lens	Focal length: f4.6-26.4mm (equivalent to 28-160mm for 35mm cameras. When setting Step Zoom, seven fixed possible steps: 28mm, 35mm, 50mm, 85mm, 105mm, 135mm, and 160mm) Aperture (F value): F 3.3 (W)-4.8 (T)
Zoom	5.7x Optical zoom ,3.6x Digital zoom
Recording Mode	Still (Continuous, S-Continuous, M-Continuous), Scene Mode (Portrait, Sports, Landscape, Nightscape, Skew Correction, Text, Zoom Macro, High Sensitivity), Movie, Sound
Recording Media	SD Memory Card (3.3V 32.64,128,256,512MB,1GB),Multi Media Card, Internal Memory (26MB)
LCD Monitor	2.5-inch Translucent Amorphous Silicon TFT LCD (approx. 153,000 pixels)
Dimensions (W x D x H)	95.0mm (W) x 26.0mm (D) x 53.0mm (H) (excluding projections)
Weight	Approx. 135g (without battery, SD memory card, and strap)
Battery	Rechargeable Battery (DB-60) x 1
Shooting Capacity*1	Based on CIPA Standard: using the DB-60, approx. 350 pictures

*1 Battery performance was measured using CIPA-standard parameters. Actual performance may vary according to usage conditions and the brand of the battery.

Caplio R40 Optional Accessories

Product Name	Model Name
Rechargeable Battery	DB-60
Battery Charger	BJ-6
AC Adapter	AC-4c
Soft Camera Case	SC-60

● Caplio is the registered trademark of Ricoh Co., Ltd. ● Microsoft, Windows and Direct X are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ● Apple, Macintosh and Mac OS are registered trademarks or trademarks of Apple Computer Inc. in the U.S. and/or other countries. ● The SD logo is a trademark. ● Compatible with EPSON PRINT Image Matching III. ● All other trademarks mentioned herein are the property of their respective owners.



For more information, visit:

http://www.ricoh.com/r_dc

RICOH

RICOH COMPANY, LTD.

3-2-3, Shin-yokohama
Kohoku-ku, Yokohama-shi 222-8530, Japan
Phone: 045-477-1738 Fax: 045-477-1797 http://www.ricoh.com/r_dc

RICOH EUROPE B.V. (PMMC EUROPE)

Oberrather Straße 6, D-40472
Düsseldorf, Germany
Phone: 0211-6546-0 Fax: 0211-6546-308 <http://www.ricohpmmc.com>

RICOH UK LTD. (PMMC UK)

Ricoh House, 1 Plane Tree Crescent, Feltham,
Middlesex, TW13 7HG, England
Phone: 0208-261-4000 Fax: 0208-261-4220

RICOH FRANCE S.A. (PMMC FRANCE)

383, Avenue du Général de Gaulle – BP 307-931-13
Clamart Cédex, France
Phone: 01-4094-3267 Fax: 01-4094-3276

RICOH ESPAÑA, S.A. (PMMC SPAIN)

Av. Litoral Mar, 12-14, 08005
Barcelona, Spain
Phone: 093-295-7600 Fax: 093-295-7605

RICOH ITALIA S.p.A. (PMMC ITALY)

via Ponchielli, 3
20063 Cernusco S/N Milano, Italy
Phone: +39-02-92361217 Fax: +39-02-92361244

RICOH HONG KONG LIMITED

Personal Multimedia Products Center
21/F., Tai Yau Building, 181 Johnston Road, Wan Chai, Hong Kong
Phone: 2862-2888 Fax: 2566-3647/2866-1120

RICOH AUSTRALIA PTY. LTD.

8 Rodborough Road, Frenchs Forrest, N.S.W. 2086 Australia
Phone: 02-8977-1111 Fax: 02-8977-1100
<http://www.ricoh.com.au>

RICOH CORPORATION

5 Dedrick Place
West Caldwell, NJ 07006 U.S.A.
Phone: 1-800-Ricoh93 <http://www.ricoh-usa.com>